Concentrating solar power research at CSIR

Thomas Roos



- Background
- CSP components and value propositions
- Progress from 2009 to date
 - Gas turbine
 - Heliostat field layout
 - Tower and thermal storage
 - Heliostat

- Way forward
 - Updated context



Background

National context: latter half of 2007


- Energy security: Eskom capacity problems just emerging
- Energy access: SHS and mini-grids showing institutional rather than technical difficulties
- Climate change: LTMS just completed, changes required to reduce SA CO₂ emissions
- No renewable incentives
- Service delivery: Sewage infrastructural and maintenance problems evident particularly in smaller towns

IRIP project

- Integrated Research Infrastructure Platform
- Sewage + sunshine → electricity, fuel and food
- Presented to and approved by CSIR Executive




What is IRIP?







Concentrating Solar portion of IRIP




IRIP: Sewage to biogas



IRIP: algal biomass



IRIP: Local Economic Development



IRIP: evolution

Initially

- scale version of full installation planned at CSIR:
 - CSP, sewage, biogas, biodiesel, fish
- CSIR seed funding, bulk of funding intended from DST/EU

But:

- DST/EU could only fund application, not R&D (so no CSP)
- Tshwane and CSIR facilities vetoed sewage onsite in 2009

So, split into two:


- "Wet works": moved off-site to sewage works (DST funding application ongoing)
- CSP: to be developed in onsite research facility (Provisionally CSIR-funded)



IRIP: CSP components & value propositions

Item	Objective	Value proposition
Gas turbine	Source COTS, install, commission	Lower capital cost, waterless, higher total efficiency (CC operation) so lower cost/kWh
Heliostat	Design, develop, implement target-aligned (TA)	Higher optical efficiency, hence fewer needed
Heliostat field	Commission layout design, develop heliostat and field control system, build	Thermal energy for 1) Turbine 2) Al smelting 3) H ₂ & thermochemistry
Thermal storage	Develop pressurised packed bed storage 1) sensible heat 2) latent heat	Extends solar-only capacity factor Reduces fuel use in hybrid mode LH reduces volume, mass and ΔP
Tower	Develop requirements, commercial contract build	Elevates receivers for better optical efficiency, houses turbine & storage
Receiver	800 C FP7: source, install Develop HT receiver	High efficiency and low ΔP Single step: 600 C to T_{target}


- Background
- CSP components and value propositions
- Progress from 2009 to date
 - Gas turbine
 - Heliostat field layout
 - Tower and thermal storage
 - Heliostat



- Way forward
 - Updated context



Gas turbine






Gas turbine



Gas turbine



• Also supplied:

- Hot air kit: high temperature "plumbing" to attach receiver to turbine
- 4 software packages



- Background
- CSP components and value propositions
- Progress from 2009 to date
 - Gas turbine
 - Heliostat field layout
 - Tower and thermal storage
 - Heliostat




- Way forward
 - Updated context



Heliostat field layout


Site chosen: NW corner of CSIR






- DLR commissioned to design field
- Tshwane height limitation on tower: 19m, or motivation with detailed plans





- Background
- CSP components and value propositions
- Progress from 2009 to date
 - Gas turbine
 - Heliostat field layout
 - Tower and thermal storage
 - Heliostat




- Way forward
 - Updated context



Tower and storage

Original concept: multiple laboratory storeys

- Power generation (top)
- Thermo-chemistry (middle)
- Student / industry (bottom)
- Ground floor: desalination, abs chiller, hoisting area




Tower and storage

Tower requirements review, due to

- Visit to PSA
 - No personnel in tower while the heliostat field is operational
 - All research experiments are controlled from the ground
 - Removes the human safety requirement
 - Large installations by commercial mobile crane, removes heavy-duty crane requirement.
- Thermal storage requirements
 - The storage subsystem will be placed in the tower
 - Thus, mass and volume of storage are needed for the tower structural design



Tower and storage




Background

CSP components and value propositions

Progress from 2009 to date

- Gas turbine
- Heliostat field layout
- Tower and thermal storage
- Heliostat




Way forward

Updated context



Heliostat design



- Background
- CSP components and value propositions
- Progress from 2009 to date
 - Gas turbine
 - Heliostat field layout
 - Tower and thermal storage
 - Heliostat

- Way forward
 - Updated context



Current Context: mid 2012

Government departments

- DWEA/DIRCO (COP15, COP17), DoF (carbon tax): CO₂ is on the table
- DoE/NERSA (IRP → REBID), DTI (IPAP, Green Jobs) : CSP has a market
- DST: Solar CoC study (2010, 2012), SETRM Workshop held Monday 18 June
- SANEDI (DoE) / TIA (DST): Investigating a centralised national CSP research facility
- DoD: SAAF engaging CSIR about wind farms & radar, and CSP & pilot safety, IR missiles
- DEA: Green Fund R800 million!

Parastatals & listed companies

- Eskom: 100MW CSP tower plant: EOI's for EPC services being assessed
- Abengoa: 50MW CSP tower plant
- Sasol: Performing FEED with BrightSource for tower CSP plant



Thank you for your attention

